

IQeye Sentinel™

SERIES



All-Weather Megapixel IP Camera

The IQeye Sentinel Series is the first All-Weather Megapixel Network Camera that is entirely Power-Over-Ethernet. The integrated, vandal and tamper-resistant design is based on the popular IQeye 700/750 camera. Sentinel's exclusive pivoting arm allows you to use the same camera for wall, ceiling or parapet mounting with no additional hardware. The entire unit is designed to withstand the harshest weather conditions, including hot, cold and wet environments.

The IQeye Sentinel series comes in multiple resolution options from 1.3 to 5 megapixels, and is available in both standard and day/night configurations. A wide variety of high quality lenses are available so Sentinel can deliver superb images in any application. With the XT option, Sentinel becomes an extreme weather camera, operating from teeth-chattering cold to searing heat with even better protection from the elements. *IQeye, when you can't afford to miss a thing.*



www.iqeye.com

IQinvision 
When you can't afford to miss a thing.

IQeye Sentinel™ Series



High Resolution

IQrecorder™

Available with every IQeye, IQrecorder enables you to record and playback crisp, clear IQeye Resolution™ images using affordable network storage *with no client software*.



IQauthenticate™

Every IQeye is also available with on-camera, digital authentication that protects images right in the camera. IQauthenticate addresses the image manipulation problem, *at the source*, ensuring your evidence has not been compromised.



IQeye Resolution

- -22°F/-30°C to 122°F/50°C
- XT option -58F/-50C to 131F/55C
- IP66 / NEMA 5
- XT option IP67 / NEMA 6
- 1.3 Mpix resolution @ 30 ips
- 2.0 Mpix resolution @ 20 ips
- 3.1 Mpix resolution @ 12 ips
- 5.0 Mpix resolution @ 10 ips
- < 0.05 lux IR Sensitive (850 Series)
- MultiStream low BW + hi resolution
- IEEE 802.3af - Power-Over-Ethernet
- 360° Pan, 180° Tilt
- LIGHTGRABBER II™ low-light feature
- Digital image cropping
- Alarm IO
- <6 watts Power-Over-Ethernet, AC or DC
- Privacy zones
- Day/Night with removable IR cut filter

CAMERA MODEL	LENS OPTIONS	POWER SUPPLY	ENCLOSURE
 IQ8xx Series IQ811 - 1.3 MP Camera, 30ips, 0.1 lux IQ802 - 2.0 MP Camera, 20ips, 0.2 lux IQ803 - 3.1 MP Camera, 12ips, 0.3 lux IQ805 - 5.0 MP Camera, 10ips, 0.3 lux	V1 - Wide Varifocal Lens V2 - Telephoto Varifocal Lens V7 - Wide Varifocal 3MP IR Corrected Lens	NP - No Power Supply PE - IEEE 802.3af PoE Module	SS - PoE Sentinel Enclosure XT - Extreme Weather Enclosure
 IQ85x Day/Night Series IQ852 - 2.0 MP Day/Night Camera, 20ips IQ853 - 3.1 MP Day/Night Camera, 12ips IQ855 - 5.0 MP Day/Night Camera, 10ips	V5 - Wide Varifocal Lens V6 - Telephoto Varifocal Lens V7 - Wide Varifocal 3MP IR Corrected Lens	NP - No Power Supply PE - IEEE 802.3af PoE Module	SS - PoE Sentinel Enclosure XT - Extreme Weather Enclosure

Example - **IQ853V6PESS** - 3.1 MP Day/Night Camera, Telephoto Lens, PoE Injector, Standard Enclosure Part Number - **IQ853⇒V6⇒PE⇒SS**

©2007 IQinVision, Inc., IQinVision, IQeye logo are registered trademarks, and IQeye, IQpoet, IQauthenticate, IQrecorder, Resolution-On-Demand, IQeye Resolution and LIGHTGRABBER are trademarks of IQinVision. All other brands, trademarks and/or registered trademarks are property of their respective holders. 0507

When you can't afford to miss a thing.